



Premstätten, February 22, 2018

## Customer Information CN03-2018

### Change to device characteristics and ordering code in the ENS210 datasheet

Dear Customer,

Please be informed that ams has changed the ENS210 datasheet which affects the following products:

- ENS210-LQFM
- ENS210-LQFT

More details on datasheet changes as follows:

#### Electrical Characteristics:

The typical value for supply current ( $I_{DD}$ ) have been updated in figure 6 per below:

Conditions	From	To
Standby state	0.04 (0.3) $\mu$ A	0.04 (0.5) $\mu$ A
Continuous run mode	58 (56) $\mu$ A	58 (61) $\mu$ A
T and RH measurement at 1Hz	7.1 (6.9) $\mu$ A	6.6 (7.1) $\mu$ A

#### Relative Humidity Sensor Characteristics:

The typical values for Relative Humidity Accuracy ( $H_{ACC}$ ) have been added to Figure 8 and Figure 14. In addition, the typical value for Relative Humidity Hysteresis in figure 8 has been updated from  $\pm 1$  %RH to  $\pm 0.7$  %RH.



**System Timing Characteristics:**

The conversion times ( $t_{CONV}$ ) in figure 9 have been updated to include T only / T and RH typical and maximum values for single shot and continuous conditions.

**Ordering & Contact Information:**

Ordering code ENS210-LQFT is not supported and has been removed from the datasheet.

**Qualification Strategy:**

No qualification required.

**Target Date of Implementation:**

22<sup>nd</sup> February 2018

**Sample Availability:**

No change to fit, form and function of the product. Samples available for customer evaluation and qualification.

**Risk Assessment:**

Low

If you do have further questions, please do not hesitate to contact me.

Best Regards,

A handwritten signature in black ink that reads "Paul Wilson".

Paul Wilson  
ams AG  
Senior Marketing Manager