ams AG Tobelbader Strasse 30 8141 Pemstaetten Austria T +43 3136 500-0 F +43 3136 525-01 sensors@ams.com www.ams.com



Premstätten, May 1, 2018

Customer Information CN18-2018

Minor updates to the CCS811 datasheet

Dear Customer,

Please be informed that ams has implemented minor updates to the CCS811 datasheet which affects the following products:

- CCS811B-JOPD500
- CCS811B-JOPR5K

More details on datasheet changes as follows:

- 1. General Replaced all references to TVOC with eTVOC
- 2. Absolute Maximum Ratings Page 5, Moved parameter for Product Lifetime (LT) to Figure 6
- Early-Life Use (Burn-In) Page 8, updated text to state "CCS811 controls the burn-in period allowing eCO₂ and eTVOC readings to be used from first power-on after 60minutes of operation in modes 1-3"
- 4. eTVOC Page 8, Changed maximum output range from 64000ppb to 32768ppb
- 5. eCO₂ Page 9, Changed maximum output range from 64000ppm to 32768ppm



Qualification Strategy: No qualification required.

Target Date of Implementation: Effective immediately

Risk Assessment:

Low

If you do have further questions, please do not hesitate to contact me.

Best Regards,

Paul Wilson ams AG Senior Marketing Manager